








CX-15



specification


model	CX-15
rated impedance	8 Ω
operation mode	passive
power handling capacity passive AES/peak*	800W / 2400W*
available frequency response**	50Hz-20kHz
max. sound pressure level***	133dB
directivity (h x v)	50° x 70°
LF-transducer rated size	15"
LF-transducer voice coil diameter	76mm/3"
LF-transducer magnet structure	ferrite
HF-compression driver rated size (VC)	45mm/1.75"
HF-compression throat diameter	1"
HF-compression magnet structure	ferrite
dimension h/w/d in mm	580/445/406
weight	25kg

* peak 10ms, with TD-8000 amplifier and CX-15 max controller setup


** -10dB with CX-15 FR controller setup

***1m free field, pink noise, crest factor 10dB, with TD-8000 and CX-15 SPL controller setup


small variety of wide range for bass cabinets extension



Disco and Pub



Live-music and touring



Touring and installation

Features CX-15

- 1x15"/1.75" coaxial speaker
- 15" transducer 76mm /3" voice coil
- 15" transducer ferrite magnet
- compression driver 1.75"/45mm voice coil
- compression driver ferrite magnet
- high frequency horn 1" throat
- horn directivity 50° x 70°
- multifunction housing
- wedge angle 30° and 60°
- 2 M10 mounting points
- 2 multi gauge plate 360° / 5° steps
- tripod (pole mounting) flange
- 4 Neutrik speakon 4-pin
- speakon terminals at 3 sides of the cabinet
- bass link function
- high-mid link function
- perforated steel front grill powder coated
- acoustic foam 4mm behind front grill
- wood housing plywood 15mm
- polyurea (PU) high scratch proof coating

Appliance CX-15

- high-mid unit for fix installation
- floor monitor
- near fill
- delay line

Application CX-15

- discotheque, clubs, bars, entertainment
- live events, live entertainment